





A

10/05/98



# UTILITY PATENT APPLICATION TRANSMITTAL

Only for new nonprovisional applications under 37 CFR 1.53(b)

Attorney Docket No.

36J.P164

First Named Inventor or Application Identifier

Gregory F. Beck, et al.

Express Mail Label No.

GB20198430XUS

## APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

## ADDRESS TO:

Assistant Commissioner for Patents  
Box Patent Application  
Washington, DC 20231

1. ☒ Fee Transmittal Form  
(Submit an original, and a duplicate for fee processing)

2. ☒ Specification *Total Pages*

3. ☒ Drawing(s) (35 USC 113) *Total Sheets*

4. ☒ Oath or Declaration *Total Pages*

a. ☐ Newly executed (original or copy)

b. ☒ Unexecuted for information purposes

c. ☐ Copy from a prior application (37 CFR 1.63(d))  
(for continuation/divisional with Box 17 completed)  
[Note Box 5 below]

i. ☐ **DELETION OF INVENTOR(S)**  
Signed Statement attached deleting  
inventor(s) named in the prior application,  
see 37 CFR 1.63(d)(2) and 1.33(b).

5. ☐ Incorporation By Reference (useable if Box 4c is checked)  
The entire disclosure of the prior application, from which a copy  
of the oath or declaration is supplied under Box 4c, is considered  
as being part of the disclosure of the accompanying application  
and is hereby incorporated by reference therein.  
"Express Mail" mailing label number **98201 984 30X US**

Date of Deposit **OCT 5, 1998**

I hereby certify that this paper or fee is being deposited with  
the United States Postal Service "Express Mail Post Office to  
Addressee" service under 37 CFR 1.10 on the date indicated above  
and is addressed to the Commissioner of Patents and Trademarks,  
Washington, D. C. 20231.

**MICHAEL K. O'NEILL**

(Typed or printed name of person mailing paper or fee)

(Signature of person mailing paper or fee)

6. ☐ Microfiche Computer Program (Appendix)

7. Nucleotide and/or Amino Acid Sequence Submission  
(if applicable, all necessary)

a. ☐ Computer Readable Copy

b. ☐ Paper Copy (identical to computer copy)

c. ☐ Statement verifying identity of above copies

## ACCOMPANYING APPLICATION PARTS

8. ☐ Assignment Papers (cover sheet & document(s))

9. ☐ 37 CFR 3.73(b) Statement (when there is an assignee) ☒ Power of Attorney

10. ☐ English Translation Document (if applicable)

11. ☒ Information Disclosure Statement (IDS)/PTO-1449 ☒ Copies of IDS Citations

12. ☐ Preliminary Amendment

13. ☒ Return Receipt Postcard (MPEP 503)  
(Should be specifically itemized)

14. ☐ Small Entity ☐ Statement filed in prior application  
Statement(s) Status still proper and desired

15. ☐ Certified Copy of Priority Document(s)  
(if foreign priority is claimed)

16. ☐ Other: \_\_\_\_\_

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No. \_\_\_\_/\_\_\_\_

## 18. CORRESPONDENCE ADDRESS

☒ Customer Number or Bar Code Label **05514** (Insert Customer No. or Attach bar code label here) or ☐ Correspondence address below

NAME

Address

City

State

Zip Code

Country

Telephone

Fax



CLAIMS	(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS		
	TOTAL CLAIMS (37 CFR 1.16(c))	38-20 =	18	X \$ 22.00 =	\$396.00		
	INDEPENDENT CLAIMS (37 cfr 1.16(b))	10-3 =	7	X \$ 82.00 =	\$574.00		
	MULTIPLE DEPENDENT CLAIMS (if applicable) (37 CFR 1.16(d))			\$270.00 =	\$		
				BASIC FEE (37 CFR 1.16(a))	\$790.00		
Total of above Calculations = \$1,760.00							
Reduction by 50% for filing by small entity (Note 37 CFR 1.9, 1.27, 1.28).							
TOTAL = \$1,760.00							

19. Small entity status

- a. ☐ A Small entity statement is enclosed
- b. ☐ A small entity statement was filed in the prior nonprovisional application and such status is still proper and desired.
- c. ☐ Is no longer claimed.


20. ☒ A check in the amount of \$ 1,760.00 to cover the filing fee is enclosed.

21. ☐ A check in the amount of \$ \_\_\_\_\_ to cover the recordal fee is enclosed.

22. The Commissioner is hereby authorized to credit overpayments or charge the following fees to Deposit Account No. 06-1205:

- a. ☒ Fees required under 37 CFR 1.16.
- b. ☒ Fees required under 37 CFR 1.17.
- c. ☐ Fees required under 37 CFR 1.18.

**SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT REQUIRED**

NAME	Michael K. O'Neill, Reg. No. 32,622
SIGNATURE	
DATE	October 5, 1998

"Express Mail" mailing label number GB 201 984 30X US

Date of Deposit OCT 5, 1998

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Commissioner of Patents and Trademarks, Washington, D. C. 20231.

MICHAEL K. O'NEILL

(Typed or printed name of person mailing paper or fee)

Michael K. O'Neill

(Signature of person mailing paper or fee)

## CHANNEL PROTOCOL FOR IEEE 1394 DATA TRANSMISSION

### BACKGROUND OF THE INVENTION

#### Field Of The Invention

The present invention relates to a system for transmitting and receiving data over a bus in which the data is formatted in IEEE 1394 standard and in which the data is sent and received over the same IEEE 1394 channel.

#### Incorporation By Reference

This application incorporates by reference commonly assigned U.S. Patent Application No. \_\_\_\_\_, entitled "Digital Video Network Interface" (internal reference No. MOI-328/360), the disclosure of which is herein incorporated by reference, as if set forth in full.

#### Description Of The Prior Art

The IEEE 1394 standard bus (1394 bus) provides for isochronous transmission of data packets, which are sent and received every 125

microseconds in correspondence to one cycle. A maximum of 64 isochronous packets can be sent over the bus per cycle. As a result, any device that uses the IEEE 1394 standard for isochronous transmission of data, is assigned an isochronous channel, ranging in value from 0 to 63. The channel is assigned to a specific device until it is released by that device. In this regard, when the 1394 bus is initialized, a node identifier is automatically assigned to each device (such as a digital video camera) that uses the bus as a means of identifying each node.

To achieve isochronous transmission on plural channels, the IEEE 1394 specification (IEEE 1394-1995) reserves one of the plural nodes connected to the bus so that it is used for isochronous resource management, a function that is supported by a software layer (to be discussed in greater detail below). This node is known as the "Isochronous Resource Manager". The Isochronous Resource Manager manages the channel numbers used for isochronous transmission, and the time remaining in each cycle that is usable for isochronous transmission. This available remaining time to transfer additional isochronous data within each cycle is called channel bandwidth. The Isochronous Resource Manager reserves the channel bandwidth and channel numbers (0-63) needed by 1394 bus nodes for isochronous transmission. Upon power-up, each device (node) that needs to transmit data isochronously issues a request to the Isochronous Resource Manager. In particular, a node designed to transmit isochronous data must first determine if there is an unused channel and available bandwidth for that purpose. The node typically makes a request to the Isochronous Resource Manager to determine if there are isochronous channels

available and bandwidth available, in order to obtain a unique channel and bandwidth allocation.

In the case that two or more nodes desire to use the same channel, the first node requesting access to an available channel will be assigned that channel. For example, if two nodes request access to channel 63, only the node whose request reaches the Isochronous Resource Manager first will be assigned to channel 63. All other nodes will be locked out from using channel 63 until the device using channel 63 releases the channel.

The problem of attempting to use the same channel occurs not only when more than 64 devices are attempting to access the 1394 bus, but can also arise even if only two or more digital video cameras are being used on the same 1394 bus. That is, many different digital video cameras are designed to transmit over a single preset channel number, or "broadcast channel" for transmitting digital video data packets over the 1394 bus. The "broadcast channel" concept is described in U.S. Patent No. 5,535,208, entitled "Data Transmission System And Method", Kawakami et al, assigned to Matsushita. This broadcast channel, as defined by this patent, has in practice become the first available isochronous channel, or channel 63. However, because the IEEE 1394 standard does not allow more than one node to use the same isochronous channel at one time, only one of the digital video cameras is permitted isochronous bandwidth and use of channel 63 to perform transmission of isochronous data on the bus. As a result of this conflict, two or more digital video cameras connected to the same 1394 bus cannot be used in a bi-directional video conferencing configuration, because at the sending and receiving sides, only one camera will be able to send data per bus.

Therefore, in any configuration where multiple digital video cameras (which have adopted the "broadcast channel" concept standard of U.S. Patent No. 5,535,208) are attempting to transmit  
5 isochronous data on a 1394 bus, only one camera will be able to send isochronous data and all others will be locked out from sending isochronous data on the bus.

Although the problems with the assignment  
10 of channels have been disclosed with respect to digital video cameras, it should be understood that the same problem applies in the case of other IEEE 1394 devices, such as scanners, digital video disks, compact disks, set-top boxes, computers, or any  
15 other devices that wish to isochronously transmit data on conflicting channels. Also, this problem would apply in the case that all 64 channels have been already assigned and a new device is attempting to utilize a channel that has already been assigned.

Heretofore, it has not been possible to  
20 send/receive data over the same 1394 bus when more than one device is attempting to use a single broadcast channel, for example, channel 63, of the 1394 bus. Accordingly, it is desirable to have a  
25 system that permits two or more devices to transmit or receive data using the same channel over a 1394 bus, so that transmitting data over a local data bus or a local area network by more than one device using the same broadcast channel becomes possible.

30

#### SUMMARY OF THE INVENTION

It is an object of the present invention to provide a network interface which can interface with a local data bus or local area network and at least  
35 two peripheral devices which share identical IEEE 1394 broadcast channels. The present invention provides an individual 1394 bus for each device

using the network interface together with its own 1394 link layer.

Thus, according to one aspect of the invention, a system for transmitting and receiving data formatted in IEEE 1394 standard between devices using a same IEEE 1394 broadcast channel includes a CPU interfaced to a bus, a first 1394 interface connected to the bus via first physical and link layers, and a second 1394 interface connected to the bus via second physical and link layers. The CPU is configured for 1) receiving data from the bus, prefixing a header to the received data and retransmitting the received data with the prefixed header onto the bus, and 2) receiving data prefixed with a header, interpreting the header to identify which of the first or second interfaces should receive the data, and transmitting the data over the bus to the identified 1394 interface.

According to another aspect of the invention, in a system for transmitting and receiving data formatted in IEEE 1394 standard between devices using a same IEEE 1394 broadcast channel, the system includes a CPU interfaced to a bus, a first 1394 interface connected to the bus via first physical and link layers, and a second 1394 interface connected to the bus via second physical and link layers. The CPU is configured for receiving data over the bus and routing the data to either the first or second 1394 interface based on the received data.

In yet another aspect of the invention, the present invention provides a configuration in which two or more digital video cameras, which transmit/receive data over the same IEEE 1394 broadcast channel, can be used in a video conference system. According to this aspect of the invention, a network video conferencing system includes at

09166488.100598

least one digital video camera for transmitting digital video data and at least one digital video camera for receiving digital video data at a local side, and at least one digital video camera for transmitting digital video data and at least one digital video camera for receiving digital video data at a remote side. All digital cameras at both the local side and the remote side use the same IEEE 1394 broadcast channel to transmit data. The network video conferencing system includes a local CPU interfaced to a local data bus, a first 1394 interface connected to a first digital video camera and connected to the local data bus via first physical and link layers, a second 1394 interface connected to a second digital video camera and connected to the local data bus via second physical and link layers, a network interface connected to the local data bus and to a local area network, a remote network interface connected to a remote data bus and the local area network, a remote CPU interfaced to the remote data bus, a third 1394 interface connected to a third digital video camera and connected to the remote data bus via third physical and link layers, and a fourth 1394 interface connected to a fourth digital video camera and connected to the remote data bus via fourth physical and link layers. The local CPU is configured to 1) receive data output by the first digital camera from the first 1394 interface over the bus, prefix a header to the received data, and retransmit the received data over the bus to the network interface which transmits the data over the local area network to the remote network interface; and 2) receive data prefixed with a header over the local data bus from the network interface, interpret the header to identify which of the first or second 1394 interfaces should receive the data, and



transmit the data over the local data bus to the identified 1394 interface which outputs the data to the at least one receiving digital video camera. The remote CPU is configured to 1) receive data off the remote data bus which has been transmitted over the local area network and which has been prefixed with a header, interpret the header to identify which of the third or fourth 1394 interfaces should receive the data, and transmits the data over the remote data bus to the identified 1394 interface for outputting at the at least one receiving digital video camera; and 2) receive data from the remote data bus which has been output from the at least one transmitting digital video camera via the third or fourth 1394 interface, prefix a header to the received data, and retransmit the received data with a prefix header onto the remote data bus which outputs the data with the prefix header to the remote network interface for output to the local area network.

These and other features and advantages according to the present invention will be more readily understood by reference to the following detailed description of the preferred embodiment taken in conjunction with the attached drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a block diagram of an IEEE 1394 network interface implemented in a bi-directional video conferencing system according to the present invention;

Figure 2 is a block diagram of the 1394 network interface according to the present invention;

Figure 3, comprising Figures 3A-3D, are a IEEE 1394 formatted isochronous data packet, an 1394 data field, a modified data packet with routing

header and ID information, and a network packet containing network header information, routing information and data packet, respectively;

5 Figure 4, comprising Figures 4A and 4B, is a flowchart depicting the transfer and receipt of video data in the bi-directional video teleconferencing system according to the present invention;

10 Figure 5 is a 1394 network interface system according to a second embodiment of the present invention;

15 Figure 6 is a modified 1394 formatted data packet containing header with ID and link layer routing information and a subheader which includes additional channel routing information; and

Figure 7 is a block diagram of a 1394 network interface according to the second embodiment of the present invention.

20 DETAILED DESCRIPTION OF THE INVENTION

Figure 1 is a block diagram representing a 1394 network interface for transferring and receiving data across a local area network from devices which send/receive data over the same IEEE 1394 broadcast channel. The 1394 network interface according to the present invention, shown in Figure 1, is implemented within a bi-directional video conferencing system.

30 Shown in Figure 1 is digital video (DV) camera 1, which may be a Canon Optura digital video camera or the like. In the present example, DV camera 1 is used for transmitting full motion digital video which includes both audio and video segments. DV camera 1 includes an IEEE 1394 interface connection. The IEEE 1394 interface connection is connected to a 1394 network interface 3 via an IEEE 1394 serial cable 2. The IEEE 1394

serial cable 2 carries packets of digital video data to the 1394 network interface 3. The video conferencing system shown in Figure 1 also includes DV camera 4 which, in the present embodiment, receives full motion digital video data, decodes the data, and transmits the data in analog form to monitor 5 for audio and for display. Monitor 5 can be any type of monitor or television having an S-Video NTSC or other connection for receiving analog audio and video.

DV camera 4 receives digital video in data packets via IEEE 1394 cable 6 from 1394 network interface 3. Preferably, the digital video data which arrive in data packets are received by network interface 3 from local area network 7. However, it is possible that DV camera 4 could receive digital video data locally from DV camera 1. Digital video camera 4 decodes the digital video data packets and outputs the analog audio and video data to monitor 14. Monitor 14 can be any type of monitor or television which has an S-Video, NTSC or other connection for receiving analog audio and video data.

Depending on their configuration, DV cameras 1 and 4 can transmit/receive video data via 1394 network interface 3. 1394 network interface 3 has at least two 1394 interface connections for connecting with each 1394 serial cable connected to DV cameras 1 and 4 and has a network interface connection which connects to local area network 7.

In order to transmit large volumes of data, which is typically needed for transmitting digital video data, it is preferable that network 7 is a Gigabit Ethernet network. In this regard, U.S. Patent Application No. \_\_\_\_\_, entitled "Digital Video Network Interface", describes the method and system for interfacing 1394 network interface 3

between digital video cameras and a local area network, such as a Gigabit Ethernet network. Briefly, as described in that application, each of network interfaces 3 and 8 include send and receive buffers, which operate to buffer and translate isochronously-timed data to and from the asynchronously-timed data of the Gigabit Ethernet. The reader is directed to the disclosure in that document for further detailed explanation regarding communication between a 1394 network interface according to the present invention and local area network 7.

In the present embodiment, 1394 network interface 3 is implemented within a bi-directional video conferencing system. A transmitting DV camera and the receiving DV camera are connected at each end of local area network 7. This allows for simultaneous transmission and reception of audio/video from a local location to a remote location. As mentioned above, a Gigabit Ethernet network is preferably employed as local area network 7 since the data transfer rate per channel is very high, typically in a range of 30 Mbits/sec. As will be discussed below in greater detail with respect to Figure 2, 1394 network interface 3 provides for the transmission and reception of data packets for devices that transmit/receive over the same IEEE 1394 broadcast channel. In the case where each of DV cameras 1 and 10 are set to transmit using channel 63 and cameras 4 and 11 are set to receive using channel 63, the 1394 network interface 3 resolves the problem of two devices, in the present case, DV camera 1 and DV camera 4, attempting to send and receive different data over the same broadcast channel 63 on the same 1394 bus. As will be discussed below, two separate 1394 buses are implemented to overcome channel conflicts.

Returning to Figure 1, 1394 network interface 3 transmits/receives data packets over local area network 7 to/from 1394 network interface 8. 1394 network interface 8, which is at the remote side of local area network 7, acts in a similar fashion to 1394 network interface 3, and includes at least two IEEE 1394 interface connections and connects to 1394 serial bus cables 9 and 13. Cable 9 is connected with DV camera 10 which, in the present example, is a transmitting video camera for transmitting digital video data over the network through 1394 network interface 8. DV camera 11, in the present example, is used as a receiving camera for receiving and decoding digital video packets which output from 1394 interface network 8 through IEEE 1394 serial cable 13. After decoding each data packet, DV camera 11 outputs digital video in analog format directly to monitor 14 for viewing.

Figure 2 is a block diagram depicting the internal hardware components of 1394 network interface 3. (1394 network interface 3 and 1394 network interface 8 are identical in hardware and in software and, therefore, a description of 1394 network interface 8 will not be presented for the purposes of brevity.)

Shown in Figure 2 is DV camera 1 which is connected through 1394 cable 2 to 1394 network interface 3. According to the present invention, 1394 network interface 3 can be a stand-alone network card or can reside within a personal computer or the like. 1394 network interface 3 includes at least two 1394 interface connections for connecting with each of the DV cameras 1 and 4 and also includes a network interface connection for connecting to the local area network 7. 1394 network interface 3 receives data from DV camera 1

through its IEEE 1394 interface into 1394 physical layer 20.

Physical layer 20 is an IEEE 1394 hardware connection which provides electrical and mechanical  
5 interaction with 1394 cable 2. Link layer 21, which is connected to physical layer 20, is an IEEE 1394 interface link which receives 1394 formatted data, controls access to the 1394 bus, assigns channels to  
10 nodes using the bus (when, as here, the link layer is the isochronous resource manager), and verifies accuracy of the 1394 data packets. In addition, and under control of software, link layer 21 interprets the data and routes the data based on header information in the 1394 data packet. In this  
15 regard, the IEEE 1394 standard format for a data packet will be discussed in greater detail with respect to Figures 3A-3D.

After receiving and interpreting the data packet, link layer 21 transmits the data over bus 22  
20 which preferably is a Peripheral Component Interconnect (PCI) bus. PCI bridge 24 manages the flow of data through PCI bus 22 which connects components together in 1394 network interface 3, such as all 1394 link layers, CPU (Central  
25 Processing Unit) 28, random access memory (RAM) 29, network controller 30, and other components within 1394 network interface 3. In the present example, data packets that are received from local area network 7 are routed by PCI bridge 24 to link layer  
30 26 (indirectly, through RAM 29) which outputs the data to physical layer 25. Physical layer 25 outputs the data packets through its electrical connection to DV camera 4, via the IEEE 1394 connection and 1394 cable 6. Prior to routing the  
35 data packet from RAM 29 through PCI bridge 24 to link layer 26, CPU 28 interprets information in the data packets to identify the source and recipient

091649 100598

and, based on the information, routes the data packet to the intended recipient.

5       Upon receiving the data packet from local area network 7, network controller 30 transfers the data packet through the PCI bus via PCI bridge 24 which routes it to RAM 29. Network driver software, which operates in conjunction with network controller 30, removes network header information and unpackages the data from its network protocol  
10       format. CPU 28 outputs the data onto PCI bus 22 via PCI bridge 24, routed to the intended recipient. A 1394 header is added by the link layer to the data packet based on the source of the data packet and based on the intended recipient of the data packet.  
15       In the present embodiment, since DV camera 4 is the receiving camera, The 1394 header is added by link layer 26.

As mentioned previously, all DV cameras 1, 4, 10 and 11 have the same preset broadcast channel:  
20       broadcast channel 63. This causes a conflict when two or more DV cameras are attempting to transmit over the same 1394 bus. As discussed above, each 1394 link layer controls access to its bus to transmit and prevents more than one transmitter from  
25       using the same broadcast channel on the bus. In the present invention described with respect to Figure 2, the conflict of two or more devices, such as DV cameras, at either side transmitting data over the same 1394 channel is addressed by providing more  
30       than one 1394 physical layer, 1394 link layer, and 1394 bus. Without such a solution, there would be a conflict between DV cameras attempting to transmit data over the same 1394 bus. In this regard, each link layer 21 and 26 receives data packets from each  
35       device in an IEEE 1394 standard format. In a videoconferencing environment, only one camera such as camera 1 transmits while the other camera (camera

09165488 100598

4) receives. The channel 63 conflict occurs because camera 4 is intended to receive video data from a remote camera, but what it actually receives (because of the conflict) is video data from local camera 1.

Figure 3A illustrates a typical 1394 data packet. The fields and headers of the data packet have the following definitions:

5		Header:	includes fields for data length,
10			tag, channel, tcode and sy, all of which are described below.
	Data_length:		is the length of data in bytes.
	tag:		is the tag field, which defines the type of data being
15			transmitted, i.e., digital video, facsimile data, etc.
	channel:		is the channel field which specifies the 1394 channel that
20			this packet is being transmitted on. As mentioned previously, IEEE 1394 standard provides for
			64 channels numbered 0-63.
	tcode:		is the transaction code that specifies what type of
25			transaction shall be performed on the packet.
	sy:		is the synchronization code which is application specific.
	header CRC:		the CRC (Cyclical Redundancy Check) is provided to verify that
30			



the header was transmitted accurately.

data field: contains the data for the packet.

5 data CRC: the CRC (Cyclical Redundancy Check) is provided to verify that the data was transmitted accurately.

Upon receiving the 1394 data packet, physical layer 20 transmits the data packet to link layer 21. Link layer 21 and its software support interpret the data in the data packet and remove all non-data information including the header before transmitting a data packet which contains just the data field, shown in Figure 3B. That is, link layer 15 21 strips off the 1394 header, the header CRC and the data CRC prior to forwarding the data packet onto PCI bus 22 via PCI bridge 24 which forwards the data packet to RAM 29 for use by CPU 28. When the data packet containing the data field is received, 20 CPU 28 attaches to the data field an ID header, shown in Figure 3C. The ID header, which is produced by CPU 28, contains link layer routing information which informs the receiving side as to which link layer should receive the data packet. In 25 addition, the ID header includes information regarding the data and the transmitting device. After attaching appropriate header information, CPU 28 outputs the updated data packet containing the ID header onto PCI bus 22 via PCI bridge 24 which 30 routes the data packet and header to network controller 30.

In the present embodiment, it is the task of the network controller 30 to negotiate access to local area network 7 and to buffer received data 35 to/from the local area network. In addition, network controller 30 handles all timing requirements of sending/receiving data. In this

regard, on the transmitting side, network controller 30 buffers both data packets to be sent once it has access to local area network 7 and data packets which have been received from the remote location.

5 Associated network driver software either reformats or unpacks the data packets into/from specific network protocol format and, in addition, attaches/removes a network header to the data packet which already contains an ID header and data field, shown in Figure 3D. Upon receiving access to the network, network controller 30 outputs a data packet which now includes a network header, ID header and data field, shown in Figure 3D. The network header provides information that identifies the contents of the data packet and the appropriate address on the network of the receiving network interface, in the present example, 1394 network interface 8.

The method by which 1394 network interface 3 receives and transmits data packets from its 1394 interfaces over local area network 7 will now be discussed in greater detail with respect to the flowcharts illustrated in Figures 4A and 4B.

Figure 4A is a flowchart illustrating the receipt and transfer of data packets through 1394 network interface 3 to local area network 7. In step S400, 1394 network interface 3 receives a data packet from DV camera 1 via cable 2. The data packet is transmitted from physical layer 20 to link layer 21. In step S401, link layer 21 reviews the 1394 data packet, determines if it meets with the 1394 protocol and, in the case that it does, removes header information, header\_CRC information, and data\_CRC information, resulting in the data packet depicted in Figure 3B. The data packet is then forwarded to CPU 28 across PCI bus 22 via PCI bridge 24.

In step S403, based on the identity of the device that transmitted the data packet, and based on the type of data packet and the recipient of the data packet, CPU 28 modifies the data packet by  
5 attaching a routing and ID header which will direct the data packet to the intended recipient at the remote side of the local area network. The resulting data packet is depicted in Figure 3C. Once the routing and ID header has been attached to  
10 the data packet, the data packet is transferred to network driver software (step S405) which attaches a network header to the data packet and repackages the data packets for transmission over the network in accordance with network protocol standards (step  
15 S406). The resulting data packet is depicted in Figure 3D. In the case of a Gigabit Ethernet network, network driver software combines two or more (three are preferred) DV data packets together since the Gigabit Ethernet format can accept larger  
20 amounts of data in each packet than the IEEE 1394 protocol permits.

In step S407, the packaged data packets are sent to network controller 30 for transmission across the local area network. Upon receiving the  
25 data packet, network controller 30 begins to negotiate with local area network 7 for access to the network. However, as can be understood, access to the network is not guaranteed and, therefore, network controller 30 must continue to negotiate and  
30 handshake with network 7 in order to obtain access while at the same time buffering data packets in its internal transmit buffer. Once access to local area network 7 has been obtained, network controller 30 may send all the data packets in its buffer which  
35 have been repackaged into the appropriate network format and have appropriate network headers in a single burst across network 7.

Figure 4B is a flowchart illustrating the receipt and unpackaging of data packets through network interface 3. In this regard, DV camera 4 will be used in this example as the recipient of data packets sent across network 7 to 1394 network interface 3.

Upon receiving a network packet via network 7 in step S409, network controller 30 outputs data packets across the PCI bus via PCI bridge 24 to CPU 28. The network packet is unpackaged by network driver software into individual data packets in step S410. The packets are separated and the network headers are stripped off, and each data packet is reconstructed into individual data packets, each much like that shown in Figure 3C. CPU 28 removes the ID and routing header in step S411 and routes the data packet based on the ID and routing header to an appropriate 1394 link layer.

In step S413, and in accordance with the present example, the data packet is routed via PCI bus 22 to link layer 26. Upon receiving the data packet, which is now only in the format of a data field as shown in Figure 3B, link layer 26 reconstructs the data packet into a 1394 standard format by rebuilding the 1394 header, the header\_CRC, and the data\_CRC, as shown in Figure 3A. The data packet is then transmitted through physical layer 25 to the recipient device, DV camera 4, in step S414.

Although the data packet which was received by CPU 28 indicated that the data packet should be transmitted over channel 63 of the 1394 bus, CPU 28 interprets the router and ID header and identifies which of the link layers, in this example link layer 21 or 26, should receive the data packet based on the routing and ID header information supplied by the transmitting side.

A second embodiment of the present invention will now be described with respect to Figures 5, 6 and 7. In the second embodiment, each 1394 network interface is connected to more than two devices, of which at least two of the devices are using the same broadcast channel and the others may or may not be using the same broadcast channel.

As shown in Figure 5, 1394 network interface 40 is connected to multiple 1394 devices such as facsimile machine 41, DV camera 42, hard disk drive 43, and DV camera 44, which is also connected to monitor 46. Data from any one of facsimile machine 41, DV cameras 42 or 44 or hard disk drive 43 may be transmitted across local area network 7 to the receiving side, 1394 network interface 48. Network interface 48 has at least two IEEE 1394 interface connections which connect to multiple 1394 devices such as DV recorder 50, DV camera 51, scanner 52 and DV camera 55. DV camera 55, like DV camera 44, is connected to monitor 56 or the like. Data packets are sent and received from network interface 48 through local area network 7, which is preferably a Gigabit Ethernet network.

In the present embodiment shown in Figure 5, only DV cameras 42, 44, 51 and 55 are transmitting over the same broadcast channel. Therefore, each of the DV cameras is provided with its own 1394 bus, physical layer and link layer, such that two channel 63 DV cameras do not coexist on the same physical IEEE 1394 bus. In the first embodiment explained with respect to Figure 1, each link layer 21 and 26 had only one device that was transmitting or receiving data packets on channel 63. Consequently, CPU 28 in Figure 2 only had to determine which link layer, 21 or 26, was the appropriate recipient or transmitter of a data packet. In the Figure 5 embodiment, on the other

hand, CPU 28 must determine, based on header and subheader information, which link layer and which channel of that link layer should receive the data packet.

5           In the embodiment shown in Figure 5, facsimile 41, DV camera 42, and hard disk drive 43, are all interfaced with one physical layer and one link layer within 1394 network interface 40. That is, as shown in Figure 7, on the exterior of 1394  
10 network interface 40, facsimile 41, DV camera 42 and hard disk drive 43, each have a 1394 interface connection with physical layer 70 which transmits and receives data over the 1394 bus to/from link layer 71. On the other hand, DV camera 44 is  
15 connected to its own physical layer 74 and link layer 75 in 1394 network interface 40.

          In order to distinguish which of the multiple devices connected to one link layer should receive a data packet, the data packet received by  
20 CPU 76 in network interface 40 must include sufficient information to allow the CPU to derive both the link layer and the channel number. For example, the header might also include a subheader. As shown in Figure 6, each data packet according to  
25 the second embodiment contains a header which indicates which link layer receives the data and a subheader which indicates a channel within the link layer which should receive the data packet. Thus, the data packet which is received by CPU 76 includes  
30 not only a header but also a subheader attached to the data field.

          A more detailed description as to how a data packet is received from the local area network and output to a 1394 interface device will now be  
35 discussed in greater detail with respect to Figure 7. Upon receiving a data packet from network 7, the data packets are stored within network interface

78's internal buffer. After data packets have been received, or as they are being received, network controller 78 outputs each data packet over the PCI bus 82 via PCI bridge 73 to RAM 79. Network driver software removes the network header and unpackages the network packets and, if necessary, separates data packets in the case more than two (here, three are preferred) DV data packets have been combined for the particular network protocol.

As mentioned above, each data packet that CPU 76 receives includes a data field, a subheader and a header, as illustrated in Figure 6. Based on the header information, CPU 76 identifies which link layer, 71 or 75, should receive the data packet. In addition, based on the subheader information, CPU 76 can identify which channel in link layer 71 or 75 should receive the data packet and, based on the channel's identity, CPU 76 provides the necessary routing information which the link layer will use to output the data packet over the correct 1394 broadcast channel. In the present example, the data packet received is intended for transmission over channel 62 which in this example is being used by hard disk drive 43.

After interpreting and removing each header and subheader, in the present example, CPU 76 transmits the data packet via PCI bridge 73 and PCI bus 82 to link layer 71. Link layer 71 rebuilds the data packet into a IEEE 1394 standard format for transmitting the data packet to hard disk drive 43 through physical layer 70.

It is because of the header and subheader information that CPU 76 determines where to route each data packet it receives from network controller 78 and controls which link layer receives the data packet, as well as which channel of the 1394 bus, controlled by that link layer, should be used to





WHAT IS CLAIMED IS:

1. A system for transmitting and receiving data formatted in IEEE 1394 standard between devices using a same IEEE 1394 broadcast channel,

5 comprising:

a CPU interfaced to a bus;

a first 1394 interface connected to the bus via first physical and link layers; and

10 a second 1394 interface connected to the bus via second physical and link layers,

wherein the CPU is configured for 1) receiving data from the bus, attaching a header to the received data, and retransmitting the received data with the prefixed header onto the bus; and 2) receiving data prefixed with a header, interpreting the header to identify which of the first or second 1394 interfaces should receive the data, and transmitting the data over the bus to the identified 1394 interface.

20

2. A system according to Claim 1, further comprising a first digital video camera having a fixed broadcast channel and which transmits/receives digital video data isochronously through the first 1394 interface and a second digital video camera having the same fixed broadcast channel as the first digital video camera and which transmits/receives digital video data isochronously through the second 1394 interface.

30

3. A system according to Claim 1, wherein the header identifies the type of data, the data recipient and amount of data.

35

4. A system according to Claim 2, wherein the digital video data output from either the first or second video camera includes 1394 header

information, data, and header and data check  
information, and wherein the link layer for each  
respective 1394 interface removes the 1394 header  
and header and data check information prior to  
5 transmitting the data over the bus to the CPU.

5. A system according to Claim 2, further  
comprising a network controller for accessing a  
local area network and for transmitting data with  
10 the header, wherein the network controller receives  
the data and the header, attaches a network header  
to the data and repackages the data with the header  
and network header into a network data packet and,  
upon receiving access to the local area network,  
15 transmits the network packet over the local area  
network to a receiving side network controller based  
on the attached network header.

6. A system according to Claim 5, wherein  
20 received network data packets are unpackaged,  
network headers are removed, and the header is  
interpreted to identify which 1394 interface should  
receive the data.

7. A system according to Claim 6, wherein  
25 the link layer of the identified 1394 interface  
attaches 1394 header and data information to the  
data and transmits the data through the physical  
layer to the identified 1394 interface in an  
isochronous manner and where, in the case the  
30 identified 1394 interface connects to the first  
digital video camera, the identified 1394 interface  
outputs the data in the isochronous manner to the  
first digital video camera and, in the case the  
35 identified 1394 interface connects to the second  
digital video camera, the identified 1394 interface

outputs the data in the isochronous manner to the second digital video camera.

5 8. A system according to Claim 7, further comprising a monitor for displaying analog video data output from either the first or second digital video camera.

10 9. A system according to Claim 1, further comprising an interface to a local area network.

10. A system according to Claim 1, wherein the bus is a PCI bus.

15 11. A system for transmitting and receiving data formatted in IEEE 1394 standard between devices using a same IEEE 1394 broadcast channel, comprising:  
a CPU interfaced to a bus;  
20 a first 1394 interface connected to the bus via first physical and link layers; and  
a second 1394 interface connected to the bus via second physical and link layers,  
wherein the CPU is configured for receiving  
25 data over the bus and routing the data to either the first or second 1394 interface based on the received data.

30 12. A system according to Claim 11, further comprising a first digital video camera having a fixed broadcast channel and which transmits/receives digital video data isochronously through the first 1394 interface and a second digital video camera having the same fixed broadcast  
35 channel as the first digital video camera and which transmits/receives digital video data isochronously through the second 1394 interface.

0946499-10059

13. A system according to Claim 12,  
wherein the digital video data output from either  
the first or second video camera includes 1394  
header information, data, and header and data check  
information and wherein the link layer for each  
respective 1394 interface removes the 1394 header  
and header data check information prior to  
transmitting the data over the bus to the CPU.

14. A system according to Claim 12,  
further comprising a network controller for  
accessing a local area network and for transmitting  
data with the header, wherein the network controller  
receives the data and the header, attaches a network  
header to the data and repackages the data with the  
header and network header into a network data packet  
and, upon receiving access to the local area  
network, transmits the network packet over the local  
area network to a receiving side network controller  
based on the attached network header.

15. A system according to Claim 14,  
wherein received network data packets are  
unpacked, network headers are removed, and the  
header is interpreted to identify which 1394  
interface should receive the data.

16. A system according to Claim 15,  
wherein the link layer of the identified 1394  
interface attaches 1394 header and data information  
to the data and transmits the data through the  
physical layer to the identified 1394 interface in  
an isochronous manner and where, in the case the  
identified 1394 interface connects to the first  
digital video camera, the identified 1394 interface  
outputs the data isochronously to the first digital

5 video camera and, in the case the identified 1394  
interface connects to the second digital video  
camera, the identified 1394 interface outputs the  
data isochronously to the second digital video  
camera.

10 17. A system according to Claim 16,  
further comprising a monitor for displaying digital  
video data output from either the first or second  
digital video camera.

15 18. A system according to Claim 11,  
further comprising an interface to a local area  
network.

19. A system according to Claim 11,  
wherein the bus is a PCI bus.

20 20. A network video conferencing system  
having at least one digital video camera for  
transmitting digital video data and at least one  
display device for receiving digital video data at a  
local side, and having at least one digital video  
camera for transmitting digital video data and at  
25 least one display device for receiving digital video  
data at a remote side, all digital cameras and  
display devices at both the local side and the  
remote side using the same IEEE 1394 broadcast  
channel, comprising:

30 a local CPU interfaced to a local data bus;  
a first 1394 interface connected to a local  
digital video camera and connected to the local data  
bus via first physical and link layers;  
a second 1394 interface connected to a  
35 local display device and connected to the local data  
bus via second physical and link layers;

a network interface connected to the local data bus and to a local area network;

a remote network interface connected to a remote data bus and the local area network;

5 a remote CPU interfaced to the remote data bus;

10 a third 1394 interface connected to a remote digital video camera and connected to the remote data bus via third physical and link layers; and

a fourth 1394 interface connected to a remote display device and connected to the remote data bus via fourth physical and link layers,

15 wherein the local CPU is configured to 1) receive data output by the local digital camera from the first 1394 interface over the bus, attach a header to the received data, and retransmit the received data over the bus to the network interface which transmits the data over the local area network to the remote network interface; and 2) receive data with an attached header over the local data bus from the network interface, interpret the header to  
20 identify which of the first or second 1394 interfaces should receive the data, and transmit the data over the local data bus to the identified 1394  
25 interface which outputs the data to the local display device, and

30 wherein the remote CPU is configured to 1) receive data off the remote data bus which has been transmitted over the local area network and which has a header attached thereto, interpret the header to identify which of the third or fourth 1394  
35 interfaces should receive the data, and transmit the data over the remote data bus to the identified 1394 interface for outputting to the remote display device; and 2) receive data from the remote data bus which has been output from the remote digital video

camera via the third or fourth 1394 interface,  
attach a header to the received data, and retransmit  
the received data with the attached header onto the  
remote data bus which outputs the data with the  
5 header to the remote network interface for output to  
the local area network.

21. A network video conferencing system  
according to Claim 20, wherein the first digital  
10 video camera transmits video data to the fourth  
digital video camera at the remote side and the  
second digital video camera receives video data from  
the third digital video camera at the remote side.

22. A network video conferencing system  
according to Claim 20, wherein the local area  
15 network is a Gigabit Ethernet network.

23. A network video conferencing system  
according to Claim 20, wherein the local and remote  
20 data busses are PCI busses.

24. A system for transmitting and  
receiving data formatted in IEEE 1394 standard  
25 between devices using a same IEEE 1394 broadcast  
channel, comprising:  
a CPU interfaced to a bus;  
a first 1394 interface connected to the bus  
via first physical and link layers; and  
30 a second 1394 interface connected to the  
bus via second physical and link layer,  
wherein the CPU is configured for 1)  
receiving data from the bus, attaching a header and  
a subheader to the received data, and retransmitting  
35 the received data with the attached header and  
subheader onto the bus; and 2) receiving data with  
an attached header and subheader, interpreting the

09166433-100633

header and subheader to identify which of the first  
or second 1394 interfaces should receive the data  
and which broadcast channel in the identified 1394  
interface should receive the data, and transmitting  
5 the data over the bus to the identified 1394  
interface.

25. A system according to Claim 24,  
further comprising a first digital video camera  
10 having a fixed broadcast channel and which  
transmits/receives digital video data isochronously  
through the first 1394 interface and a second  
digital video camera having the same fixed broadcast  
channel as the first digital video camera and which  
15 transmits/receives digital video data isochronously  
through the second 1394 interface.

26. A system according to Claim 25,  
wherein the digital video data output from either  
20 the first or second video camera includes 1394  
header information, data, and header and data check  
information and wherein the link layer for each  
respective 1394 interface removes the 1394 header  
and header and data check information prior to  
25 transmitting the data over the bus to the CPU.

27. A system according to Claim 25,  
further comprising a network controller for  
accessing a local area network and for transmitting  
30 data with the header and subheader, wherein the  
network controller receives the data and the header  
and subheader, attaches a network header to the data  
and repackages the data with the header and  
subheader and network header into a network data  
35 packet and, upon receiving access to the local area  
network, transmits the network packet over the local



area network to a receiving side network controller based on the attached network header.

28. A system according to Claim 27,  
5 wherein received network data packets are unpackaged, network headers are removed, and the header and subheader are interpreted to identify which 1394 interface and channel in that 1394 interface should receive the data.

10 29. A system according to Claim 28, wherein the link layer of the identified 1394 interface attaches 1394 header and data information to the data and transmits the data through the  
15 physical layer to the identified 1394 interface in an isochronous manner and where, in the case the identified 1394 interface connects to the first digital video camera, the identified 1394 interface outputs the data in the isochronous manner to the  
20 first digital video camera and, in the case the identified 1394 interface connects to the second digital video camera, the identified 1394 interface outputs the data in the isochronous manner to the second digital video camera.

25 30. A system according to Claim 29, further comprising a monitor for displaying analog video data output from either the first or second digital video camera.

30 31. A system according to Claim 24, further comprising an interface to a local area network.

35 32. A system according to Claim 24, wherein the bus is a PCI bus.

33. For use in a system for transmitting and receiving data formatted in IEEE 1394 standard between devices using the same IEEE 1394 broadcast channel, the system having a CPU interfaced to a bus, a first 1394 interface connected to the bus via first physical and link layers, and a second 1394 interface connected to the bus via second physical and link layers, computer process steps for controlling the system, comprising:

- a step of receiving data from the bus;
- a step of attaching a header to the received data;
- a step of retransmitting the received data with the attached header onto the bus;
- a step of receiving data with an attached header;
- a step of interpreting the header to identify which of the first or second 1394 interfaces should receive the data; and
- a step of transmitting the data over the bus to the identified 1394 interface.

34. For use in a system for transmitting and receiving data formatted in IEEE 1394 standard between devices using the same IEEE 1394 broadcast channel, the system having a CPU interfaced to a bus, a first 1394 interface connected to the bus via first physical and link layers, and a second 1394 interface connected to the bus via second physical and link layers, computer process steps for controlling the system, comprising:

- a step of receiving data over the bus; and
- a step of routing the data to either the first or second 1394 interface based on the received data.

35. For use in a system for transmitting and receiving data formatted in IEEE 1394 standard between devices using the same IEEE 1394 broadcast channel, the system having a CPU interfaced to a bus, a first 1394 interface connected to the bus via first physical and link layers, and a second 1394 interface connected to the bus via second physical and link layers, computer process steps for controlling the system, comprising:
- 5 a step of receiving data from the bus;
  - 10 a step of attaching a header and a subheader to the received data;
  - a step of retransmitting the received data with the header and subheader onto the bus;
  - 15 a step of receiving data with an attached header and an attached subheader;
  - a step of interpreting the header and subheader to identify which of the first or second 1394 interfaces should receive the data and which broadcast channel in the identified 1394 interface should receive the data; and
  - 20 a step of transmitting the data over the bus to the identified 1394 interface.
36. A system for transmitting and receiving data formatted in IEEE 1394 standard between devices using a same IEEE 1394 broadcast channel, comprising:
- 25 a controlling means interfaced to a communication means;
  - 30 a first 1394 interface means connected to the communication means via first physical and link layers; and
  - a second 1394 interface means connected to the communication means via second physical and link layers,
  - 35

wherein the controlling means is configured  
for 1) receiving data from the communication means,  
attaching a header to the received data, and  
retransmitting the received data with the attached  
5 header onto the communication means; and 2)  
receiving data with an attached header, interpreting  
the header to identify which of the first or second  
1394 interface means should receive the data, and  
transmitting the data over the communication means  
10 to the identified 1394 interface.

37. A system for transmitting and  
receiving data formatted in IEEE 1394 standard  
between devices using a same IEEE 1394 broadcast  
15 channel, comprising:  
a controlling means interfaced to a  
communication means;  
a first 1394 interface means connected to  
the communication means via first physical and link  
20 layers; and  
a second 1394 interface means connected to  
the communication means via second physical and link  
layers,  
wherein the controlling means is configured  
25 for receiving data over the communication means and  
routing the data to either the first or second 1394  
interface means based on the received data.

38. A system for transmitting and  
30 receiving data formatted in IEEE 1394 standard  
between devices using a same IEEE 1394 broadcast  
channel, comprising:  
a controlling means interfaced to a  
communication means;  
35 a first 1394 interface means connected to  
the communication means via first physical and link  
layers; and

a second 1394 interface means connected to the communication means via second physical and link layers,

5 wherein the controlling means is configured for 1) receiving data from the communication means, attaching a header and a subheader to the received data, and retransmitting the received data with the prefixed header and subheader onto the communication means; and 2) receiving data with an attached header and an attached subheader, interpreting the header and subheader to identify which of the first or 10 second 1394 interface means should receive the data and which broadcast channel in the identified 1394 interface should receive the data, and transmitting the data over the communication means to the 15 identified 1394 interface.

20

091643-100593

ABSTRACT OF THE INVENTION

A system for transmitting and receiving data formatted in IEEE 1394 standard between devices using a same IEEE 1394 broadcast channel includes a CPU interfaced to a bus, a first 1394 interface connected to the bus via a first physical and link layers, and a second 1394 interface connected to the bus via a second physical and link layer. The CPU is configured for 1) receiving data from the bus, prefixing a header to the received data, and retransmitting the received data with the prefixed header onto the bus; and 2) receiving data prefixed with a header, interpreting the header to identify which of the first or second interfaces should receive the data, and transmitting the data over the bus to the identified 1394 interface.

C-14691




FIG. 1




FIG. 2



data_length	tag	channel	tcode	sy
header_CRC				
data field				
data_CRC				

FIG. 3A




FIG. 3B



FIG. 3C



FIG. 3D




FIG. 4A

A




FIG. 4B

2025001 2249160




FIG. 5

Header	SubHeader	Data Field
--------	-----------	------------

**FIG. 6**

2025001-00000000

40




FIG. 7

COMBINED DECLARATION AND POWER OF ATTORNEY  
FOR PATENT APPLICATION

(Page 1)

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name;

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled CHANNEL PROTOCOL FOR IEEE 1394 DATA TRANSMISSION

the specification of which ☒ is attached hereto ☐ was filed on \_\_\_\_\_ as United States Application No. or PCT International Application No. \_\_\_\_\_ and was amended on \_\_\_\_\_ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR §1.56.

I hereby claim foreign priority benefits under 35 U.S.C. §119(a)-(d) or §365(b), of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT international application which designates at least one country other than the United States, listed below and have also identified below any foreign application for patent or inventor's certificate, or PCT international application having a filing date before that of the application on which priority is claimed:

<u>Country</u>	<u>Application No.</u>	<u>Filed (Day/Mo./Yr.)</u>	<u>(Yes/No)</u> <u>Priority Claimed</u>
----------------	------------------------	----------------------------	--

I hereby claim the benefit under 35 U.S.C. § 119(e) of any United States provisional application(s) listed below:

<u>Application No.</u>	<u>Filed (Day/Mo./Yr.)</u>
------------------------	----------------------------

I hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s), or § 365(c) of any PCT international application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 C.F.R. § 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

<u>Application No.</u>	<u>Filed (Day/Mo./Yr.)</u>	<u>Status</u> <u>(Patented, Pending, Abandoned)</u>
------------------------	----------------------------	--

COMBINED DECLARATION AND POWER OF ATTORNEY  
FOR PATENT APPLICATION

(Page 2)

I hereby appoint the practitioners associated with the firm and Customer Number provided below to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith, and direct that all correspondence be addressed to the address associated with that Customer Number:

**FITZPATRICK, CELLA, HARPER & SCINTO**  
Customer Number: 05514

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of Sole or First Inventor Gregory F. Beck

Inventor's signature \_\_\_\_\_

Date \_\_\_\_\_ Citizen/Subject of U.S.A.

Residence 23851 Formello

Laguna Hills, California 92653

Post Office Address c/o Canon Information Systems, Inc.

110 Innovation Drive, Irvine, California 92612

Full Name of Second Joint Inventor, if any Wei Zhou

Second Inventor's signature \_\_\_\_\_

Date \_\_\_\_\_ Citizen/Subject of People's Republic of China

Residence 46 Boulder Creek Way

Irvine, California 92602

Post Office Address c/o Canon Information Systems, Inc.

110 Innovation Drive, Irvine, California 92612

Full Name of Third Joint Inventor, if any Royce Earle Slick

Third Inventor's signature \_\_\_\_\_

Date \_\_\_\_\_ Citizen/Subject of U.S.A.

Residence 24452 Diamante

Mission Viejo, California 92692

Post Office Address c/o Canon Information Systems, Inc.

110 Innovation Drive, Irvine, California 92612

Full Name of Fourth Joint Inventor, if any \_\_\_\_\_

Fourth Inventor's signature \_\_\_\_\_

Date \_\_\_\_\_ Citizen/Subject of \_\_\_\_\_

Residence \_\_\_\_\_

Post Office Address \_\_\_\_\_